

## Sliding patch panel 1U



### Item Description

This innovative and robust 1U sliding patch panel has been designed to accept up to 3 LGX Modules or MTP/MPO Cassettes within a 1U space.

With the ability to use a full array of adaptor types it offers a flexible solution to the end user, enabling them incorporate a multi-functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 6 standard cable entry points for, loose tube, tight buffer, pre-terminated and steel tape armoured cable.

### Features/Benefits

- Up to 3 LGX MTP/MPO modules in 1U
- Multiple adaptor options available
- Individually labeled ports
- 45° open working angle
- Accepts loose tube, distribution and pre-terminated cables
- RoHS, REACH and SvHC
- Fits standard 19"

### Applications

- Data centers, premise installations, telecommunication networks
- Ethernet, fibre channel, ATM, LAN, MAN and WAN
- Data communication
- Indoor applications

## Specifications

Element	Characteristic
Height	1U (44.4mm)
Width	483mm
Depth	200mm
Net Weight	2.4kgs
Packaged Weight	2.7kgs
Packaged Dimensions	530mm (W) x 55mm (H) x 260mm (D)
IP Rating	IP20
Suitable for Adaptor Type	LGX / MTP
Number of Ports	3
Cable Entry 20mm	6
Mounting Adjustment Range	50mm
Material	Cold-rolled steel
Material Thickness	1.2mm
Material Coating	Electrostatic powder coating
Color	Black RAL 9004
Operating Temperature	-40°C to +60°C
Designed in Accordance With	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,
Compliant to	RoHS, Reach/SVHC

## Technical drawing

